



Security Management System

Model S1391

HID MicroProx Tag

Overview

The S1391 MicroProx Tag provides the convenience of proximity technology in a small disk shaped transponder. Simply attach the adhesive backed tag to any non-metallic card or device, and you instantly have a proximity card. Seamlessly upgrade from Wiegand, magnetic stripe, barium ferrite contact smart chip card or ID badge by simply adhering the tag to an existing card and make it a proximity credential. Add proximity access control capability to the users' cell phone, PDA and other non-metallic devices.

FEATURES & BENEFITS

- 125kHz proximity RF-programmable
- Universal compatibility with all HID readers
- The MicroProx Tag is the size of a coin
- Made from Lexan for durability
- Provides a consistent read range
- Up to 84 bits of data storage
- MicroProx Tags are passive (no batteries) and provide a long life with infinite reads



SPECIFICATIONS:

- Dimensions: Diameter - 1.285"
- Thickness - 0.070"
- Operating Temperature: -50F to 160F
- Weight: .04 oz.
- Read Ranges: HID MiniProx reader - up to 2.25"
HID ThinLine II reader - up to 2.5"
HID ProxPoint Plus reader - up to 2"
HID ProxPro II reader - up to 3.5"
HID MaxiProx reader - up to 4.5"

ORDERING INFORMATION:

S1391 - Proximity MicroProx Tag



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com