



Security Management System

Model SIONX

8 Input/12 Output Expansion Board

Overview

The Schlage SIONX provides 8 supervised contact inputs and 12 SP/DT relays. It snaps on to the SRCNX board. Only one SIONX board can be used per Reader Controller. The SIONX can be connected to any SRCNX-2, SRCNX-8 or SRCNX-16. Any input can be associated with any output response or a multitude of output responses.



FEATURES & BENEFITS

- 12 Two Amp Relays SP/DT
- 8 Inputs Normally Open or Normally Closed, Supervised or Unsupervised
- Contacts can be defined as alarms, door open detects, egress, or other environmental conditions
- 8 supervised or unsupervised contact inputs with dynamic current sourcing. Ideal for replacing 3rd party alarm/access panels
- Supports majority of end-of-line resistor values

SPECIFICATIONS

- Dimensions: 11" x 3" (snaps onto all Reader Controller boards)
- Power: supplied from the Reader Controller
- Ambient temperature: 0° to 60°C or 32° to 140° F.

ORDERING INFORMATION

SIONX- Input/Output expansion board



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com