



Security Management System

Model S5355K

HID ProxPro II Reader

Overview

The S5355K ProxPro II Proximity Reader has a two-piece design. Its secure potted electronics is ideal for indoor or outdoor applications. The S5355K offer a fully integrated personal identification number keypad for heightened security.



FEATURES & BENEFITS

- 125kHz transmit frequency
- Designed for mounting directly onto metal with minimal impact in read range
- Mounts directly to a single gang electrical box
- Mounts directly to glass (with optional glass kit)
- Replaceable covers
- Audiovisual indication provides multicolor LED (red/green) and beeper sounds
- Universal compatibility with all HID cards
- Made with a Polycarbonate UL 94 enclosure and provides a consistent read range

(continued)

ORDERING INFORMATION:

- S5355K - Keypad Reader with Wiegand protocol
- S5358K - Keypad Reader with Clock & Data output interfaces
- S5455AGM00 - Glass mounting kit (for all units)

FEATURES & BENEFITS *(continued)*

- Power up diagnostics and self test routine
 - The S5355K is provided with Wiegand communication protocol (must specify clock & data)
 - Over 137 billion unique codes are available
 - Pigtail connection
-

SPECIFICATIONS:

- Dimensions: 5" x 5" x 1"
- Power requirements: 10-28.5 VDC
- Power consumption: 100mA avg/120mA peak at 24VDC
- Operating temperature: -22F to 150F
- Weight: 13.6 oz.
- Cable distance (Wiegand or Clock & Data): 500' with 22AWG 5 conductor stranded with overall shield
- Read ranges: HID ProxCard II - up 95.5"
 - HID ISOProx II Card - up to 8"
 - HID DUOProx II Card - up to 8"
 - HID Smart ISO/DUOProx II Card - up to 8"
 - HID ProxKey II - up to 4"



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com