



Security Management System

Model S6005B

HID ProxPoint Reader

Overview

ProxPoint Reader - The S6005B Proximity Reader offers an attractive, compact design at an economical price. Its secure potted electronics is ideal for indoor or outdoor applications.

FEATURES & BENEFITS

- 125kHz transmit frequency
- Designed for mounting directly onto metal with no change in read range
- Audiovisual indication provides multicolor LED (red/green) and beeper sounds
- Universal compatibility with all HID cards
- Made with a polycarbonate UL 94 enclosure and provides a consistent read range
- Power up diagnostics and self test routine
- Over 137 billion unique codes are available
- Pigtail connection



SPECIFICATIONS:

- Dimensions: 3.125" x 1.720" x .66"
- Power requirements: 5-16 VDC
- Power consumption: 20mA avg/ 75mA peak at 12VDC
- Operating temperature: -22F to 150F
- Weight: 2.7 oz.
- Cable distance: 500' with 22AWG 5 conductor stranded with overall shield
- Read ranges: HID ProxCard II - up to 3"
HID ISOProx II Card - up to 2.5"
HID DUOProx II Card - up to 2.5"
HID Smart ISO/DUOProx II Card - up to 2.5"
HID ProxKey II - up to 1.5"

ORDERING INFORMATION:

- S6005B - Reader with Wiegand protocol
- S6008B - Reader with Clock & Data output interfaces (magnetic stripe)



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com