



Security Management System

Model SWSRBL

Wiegand Swipe Reader

Overview:

The SWSRBL Wiegand Reader combines innovative circuitry and rugged construction to resist vandals. The polymeric housing and epoxy potted electronics makes it ideal for indoor or outdoor applications. The reader can be mounted on a vertical surface with the slot orientation either upward or downward, facing to the left or the right.



FEATURES & BENEFITS

- Rugged polymeric housing and epoxy potted electronics
- Visual indication provides tri-colored LED
- Immune to external magnetic fields and RF signal
- Supports Wiegand interface format
- Versatile mounting configurations
- Slot width is 0.062" to 0.069"

SPECIFICATIONS:

- Dimensions: 2.3" x 5.3" x 1.7"
- Power requirements: 5-12 VDC
- Power consumption: 30 mA at 12 VDC
- Operating temperature: -40F to 160F
- Weight: 12.1 oz.
- Cable distance: 500' with 18AWG 6 conductor stranded with overall shield
- For use with code stripe layout options:
 - A long edge/right side
 - A1 long edge/left side
 - D short edge

ORDERING INFORMATION:

SWSRBL - Wiegand Reader
SWTRB - Wiegand Turnstile Reader
SWINS - Wiegand Insertion Reader
SWKEY - Wiegand Key Reader
SWPIN - Wiegand PinPad



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com