



Security Management System

Model SXF1060

Mini-Mullion Contactless Reader

Overview

The SXF1060 Mini-Mullion contactless smart card reader is attractive and cost-effective. The sleek package is well suited for door mullion or narrow stile installations.



FEATURES & BENEFITS

- Design: Attractive architectural styling
- Interoperability: compatible with all applicable 13.56 MHz ISO standards
- Mounting: Mullion or narrow stile
- Read Range: up to 3 inches
- Tri-state LED (red, green, amber): Visual indicator and audio feedback representing status and activity information
- Multiple Color Options
- Environment: Accommodates interior, exterior, metal and non-metal installation environments
- Warranty: Lifetime against defective workmanship and materials

ORDERING INFORMATION

SXF1060-XX - Mini-Mullion
Contactless Reader

SXF1060-MF - Mini-Mullion
Contactless MiFare Reader

SPECIFICATIONS

- Frequency: 13.56 MHz
- Standards: ISO 15693 and ISO 14443
- Certifications: FCC Certification, Canadian FCC Certification, UL 294 Listed (Pending), R&TTE Directive (15 EU Countries), CE Mark
- Maximum read range*: 13.56 MHz,
ISO 15693: up to 3" (7.62 cm)
ISO 14443 Mifare standard: up to 2" (5.08 cm)
* Maximum read range depends on credential type/form factor and installation conditions
- Voltage range: 5-16 VDC
- Power supply: Linear DC
- Max. current requirement: Average 50 mA DC, Peak 80 mA DC
- Cable specification: 18 AWG 6 Conductor Shielded
- System interface: Wiegand
- Cabling distance: Wiegand Output: 500 ft. (152m)
- Operating temperature: -31 to 151F (-35 to 67C)
- Physical dimensions (HWD): 4.1" x 1.72" x 1.0",
10.4 cm x 4.4 cm x 2.5 cm
- Weight: 0.4 lbs
- Material: PBT Polymer
- Color options: Charcoal and Black



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com