



# Model SA2D Camera Series

## Vandal-Proof Mobile Color Camera

### Overview

The Vandal-Proof Mobile Color Camera from Schlage offers superior durability and unmatched versatility in an all-weather camera. The camera can be used in a wide variety of indoor and outdoor applications: school buses, public transit, warehouses, offices, parking garages and much more. This distinctive design features dual viewing windows, allowing the camera to be either ceiling or wall mounted without requiring a bracket. The camera position within the enclosure is fully adjustable, increasing the range of possible viewing angles. This vandal resistant enclosure formed from stainless steel provides a rugged yet light-weight design. The camera is both dust and water resistant, and is suitable for both indoor and outdoor applications. An optional Infra-Red illuminator delivers clear images up to 50 feet away even in complete darkness.

### FEATURES & BENEFITS

- Stainless Steel Enclosure - rugged yet light weight
- Dual viewing positions - ceiling or wall mounting allows for multiple mounting options
- Lexan MR-10 viewing window - offers ultra-high impact and scratch resistance

*(continued)*



### ORDERING INFORMATION

- SA2D-04 - Vandal-Proof Mobile Color Camera with 3.6mm lens
- SA2D-06 - Vandal-Proof Mobile Color Camera with 6.0mm lens
- SA2D-08 - Vandal-Proof Mobile Color Camera with 8.0mm lens
- SA2D-04IR - Vandal-Proof Mobile Color Camera with an infra-red illuminator and 3.6mm lens
- SA2D-06IR - Vandal-Proof Mobile Color Camera with an infra-red illuminator and 6.0mm lens
- SA2D-08IR - Vandal-Proof Mobile Color Camera with an infra-red illuminator and 8.0mm lens

## FEATURES & BENEFITS *(continued)*

- Single Security Screw - cover fastens with a single tamper resistant screw
- Optional Infra-Red illuminator delivers clear images up to 50 feet away even in complete darkness
- Adjustable pan and tilt - wide range of viewing angles
- High Quality Sony Color CCDs - providing crystal clear images

## SPECIFICATIONS

### Camera Housing:

- Enclosed material: Formed stainless steel, electrically isolated from camera
- Viewing windows: Dual position, anti-glare, scratch resistant, high-impact Lexan MR-10
- Mounting options: Ceiling or Wall, no bracket required
- Enclosure size: Width 92mm/3.6"  
Length 132mm/5.2"  
Height 70mm/2.8"
- Weight: 500g/16oz
- Environmental: Designed to IP 66
- Rating: Outdoor, high-pressure water resistant
- Wiring harness 20 foot harness - video & power

### Electrical:

- Voltage range 11 VDC - 18 VDC
- Transient protection: 1.5 kW
- Camera sensitivity 0.1 lux @ F2.0 (B&W, D/N)  
0.9 lux @ F2.0 (Color)
- Power consumption: 1.8W @ 12V (B&W)  
3.0W @ 12V (Color, D/N)

### Available Lenses (specify when ordering)

Code*	Size (mm)	F-Stop	Viewing Angle(v)	Viewing Angle(h)
04	3.6	2.0	55°	74°
06	6.0	2.0	32°	42°
08	8.0	2.2	24°	32°



### Schlage

Electronic Security  
575 Birch Street  
Forestville, CT 06010 USA  
Tel 860-584-9158/866-322-1237  
Fax 860-584-2136/866-322-1233  
Tel 800-950-4573 (Toll Free Canada)  
[www.schlage.com](http://www.schlage.com)